

SAFETY & SECURITY FILMS

	% Visible Light Transmission	% Total Solar Transmission	% Total Solar Reflectance	% Total Solar Absorbance	% Visible Light Reflectance INT/EXT	Winter U-Value	% Ultraviolet Ray Protection (wavelengths 300-380nm)	% Glare Reduction	Shading Coefficient	% Solar Heat Gain Coefficient (SHGC)	% Total Solar Energy Rejection (TSER)	
Clear Series												
2M	89	83	8	9	9/9	1.07	94	1	0.98	0.86	14	
4M	90	82	8	10	9/9	1.07	99	0	0.98	0.85	15	
7M	89	82	8	10	9/9	1.07	99	1	0.97	0.85	15	
8M	89	81	9	10	10/10	1.07	99	1	0.97	0.84	16	
13M	88	80	9	11	10/10	1.06	99	2	0.96	0.83	17	
Ultra-Vision™ Series (Spectrally Selective, Neutral)												
8.5MULV40	41	30	10	60	9/11	1.05	98	54	0.56	0.48	52	
Symphony™ Series (Dual-Reflective, Neutral)												
4MSY65	66	63	8	29	9/9	1.07	97	27	0.83	0.72	28	
4MSY35	40	33	21	46	12/20	1.02	97	55	0.54	0.47	53	
6MSY35	40	33	18	49	17/17	1.05	97	56	0.56	0.48	52	
6MSY25	33	26	30	44	18/30	1.00	99	63	0.45	0.39	61	
8.5MSY50	49	44	11	45	9/12	1.05	98	46	0.66	0.58	42	
8.5MSY35	37	31	21	48	13/21	1.01	96	59	0.52	0.45	55	
8.5MSY25	31	24	30	46	18/30	1.00	97	66	0.43	0.38	62	
Silver Series (Reflective, Silver)												
4MSilver20	13	10	58	32	67/63	1.01	98	85	0.22	0.19	81	
8MSilver20	17	13	55	32	62/59	1.04	98	81	0.26	0.23	77	
Anti-Graffiti Series												
4M Anti-Graffiti	89	83	9	8	10/10	1.04	89	1	0.98	0.85	15	
6M Anti-Graffiti	89	82	9	9	10/10	1.04	90	1	0.98	0.85	15	

EASTMAN

Data captured using National Fenestration Rating Council's (NFRC) guidelines and calculated for single pane, nominal 1/4 inch (6mm) clear glass. Reported values are taken from representative product samples and are subject to normal manufacturing variances. Actual performance will vary based on a number of factors, including glass type and properties. ©2018 Eastman Performance Films, LLC. Product brands referenced herein with a ™ or © symbol are trademarks of Eastman Chemical Company or its subsidiaries. All other trademarks are the property of their respective owners. All rights reserved. No liability is accepted for errors. (04/18)