

PRODUCT	% VISIBLE LIGHT TRANSMISSION (VLT)	% TOTAL SOLAR ENERGY REJECTION (TSER)	% VISIBLE LIGHT REFLECTANCE (VLR)	% UV REJECTION	THICKNESS (Mils)
CIR™ Series (Black)					
CIR 70	72	45	9	>99	1.5
CIR 60	62	48	8	>99	1.5
CIR 50	51	51	7	>99	1.5
CIR 40	40	53	6	>99	1.5
CIR 30	34	54	6	>99	1.5
CIR 20	23	59	6	>99	1.5
CIR 5	5	62	6	>99	1.5
CarbonXP™ Series (Black)					
CXP 80	80	44	7	>99	1.5
CXP 70	65	44	7	>99	1.5
CXP 55	53	48	7	>99	1.5
CXP 45	40	50	7	>99	1.5
CXP 35	33	53	6	>99	1.5
CXP 25	23	54	6	>99	1.5
CXP 18	16	56	6	>99	1.5
CXP 5	6	59	5	>99	1.5
Carbon™ Series (Black)					
Carbon 85	85	30	7	99	1.5
Carbon 70	70	28	5	99	1.5
Carbon 55	60	32	5	99	1.5
Carbon 45	45	40	5	99	1.5
Carbon 38	42	41	5	99	1.5
Carbon 35	35	42	5	99	1.5
Carbon 25	24	43	5	99	1.5
Carbon 18	18	44	5	99	1.5
Carbon 5	6	50	5	99	1.5
InfinityOP™ Series (Neutral)					
INF 65	65	40	8	99	1.5
INF 50	53	40	10	99	1.5
INF 35	33	55	11	99	1.5
INF 20	21	60	11	99	1.5
INF 10	11	67	15	99	1.5
High Performance Series (Charcoal, Blue, Bronze)					
HP 55	60	33	8	99	1.5
HP 50	52	35	8	99	1.5
HP 40	44	43	8	99	1.5
HP 35	38	49	8	99	1.5
HP 30	30	51	8	99	1.5
HP 20	22	54	8	99	1.5
HP 15	15	56	8	99	1.5
HP 5	5	58	8	99	1.5
HP 50 Blue	55	34	8	99	1.5
HP 40 Bronze	40	45	8	99	1.5
HP 18 Bronze	18	60	8	99	1.5

PRODUCT	% VISIBLE LIGHT TRANSMISSION (VLT)	% TOTAL SOLAR ENERGY REJECTION (TSER)	% VISIBLE LIGHT REFLECTANCE (VLR)	% UV REJECTION	THICKNESS (Mils)
Standard Pro™ Series (Charcoal)					
STD Pro 88	88	22	5	99	1.5
STD Pro 50	62	29	8	99	1.5
STD Pro 40	43	34	8	99	1.5
STD Pro 35	35	36	8	99	1.5
STD Pro 20	20	39	8	99	1.5
STD Pro 15	15	43	8	99	1.5
STD Pro 5	5	46	7	99	1.5
Standard Series (Charcoal)					
STD 70	70	26	5	99	1
STD 50	50	29	5	99	1
STD 40	41	34	5	99	1
STD 35	38	38	5	99	1
STD 20	20	40	5	99	1
STD 5	8	46	5	99	1.5